

DBL MXV

5.25 inches deep.

Vertical mounting

Double Conversion Uninterruptible Power.

Traffic and Outdoor applications

Wide input voltage range of 55 to 150 without using the external batteries.

Full range continuous power conditioning for glitches swells, sags, brown outs and spikes.

Output Voltage stability of +/-1% under any and all conditions.

Hot swap the batteries during servicing without shutting down the UPS.



Specifications

MX-V 500-24	MX-V 800-24	MX-V 800-36	MX-V 1000-36	MX-V 1400-36
500 watts	800 watts	800 watts	1000 watts	1400 watts
120V	120V	120V	120V	120V
120V+/- 1%	120V+/- 1%	120V+/- 1%	120V+/- 1%	120V+/- 1%
55 to 150VAC	55 to 150VAC	55 to 150VAC	55 to 150VAC	55 to 150VAC
LCD Programmable Timer	LCD Programmable Timer	LCD Programmable Timer	LCD Programmable Timer	LCD Programmable Timer
24VDC	24VDC	36VDC	36VDC	36VDC
ECO Mode	ECO Mode	ECO Mode	ECO Mode	ECO Mode
"0" Transfer time to battery power	"0" Transfer time to battery power	"0" Transfer time to battery power	"0" Transfer time to battery power	"0" Transfer time to battery power
AC Anderson Power	AC Anderson Power	AC Anderson Power	AC Anderson Power	AC Anderson Power
DC Anderson Power	DC Anderson Power	DC Anderson Power	DC Anderson Power	DC Anderson Power
11.25H x 5.25D x 14.9W	11.25H x 5.25D x 14.9W	11.25H x 5.25D x 14.9W	11.25H x 5.25D x 14.9W	11.25H x 5.25D x 14.9W
-37 to +74 Temp range	-37 to +74 Temp range	-37 to +74 Temp range	-37 to +74 Temp range	-37 to +74 Temp range

TechPower Developments Inc.